



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



GM8

AUTOMATIC GROUT MIXER PLANT



Skid frame dimensions and weight (std. capacity)

Width	1340 mm	4'5"
Lenght	1950 mm	6'5"
Height	1770 mm	5'9"
Weight	1000 Kg	2204 lb



Technical Features

Electronic load cell weighing system / système de pesage électronique/ Wägeelektronik für Wägezellen

Max hourly capacity / capacité horaire maximum / maximale Stundenleistung	8 m³	35 gpm
--	------------------------	---------------

Electric power consumption / consommation électrique / Stromverbrauch	8 kW
--	-------------

MIXER

Max capacity / capacité maximale / maximale Kapazität	200 lt	53 gal
--	---------------	---------------

OPTIONAL HIGH CAPACITY MIXER	300 lt	80 gal
-------------------------------------	---------------	---------------

Max pump flow rate / pompe débit maximale / Pumpe maximale Durchflussrate	@1 bar	750 lt/min	198 gpm
--	---------------	-------------------	----------------

Pump motor / moteur de pompe / Pumpenmotor	5,5 kW
---	---------------

AGITATOR

Max capacity / capacité maximale / maximale Kapazität	500 lt	132 gal
--	---------------	----------------

OPTIONAL HIGH CAPACITY AGITATOR	700 lt / 1000 lt	185 gal / 264 gal
--	-------------------------	--------------------------

Electric motor / moteur électrique / elektromotor	0,75 Kw
--	----------------

AIR COMPRESSOR

Air compressor capacity / capacité du compresseur d'air/ Luftverdichter Kapazität	400 lt/min	105 gpm
--	-------------------	----------------

Air tank / réservoir d'air / luftbehälter	100 lt	26,4 gal
--	---------------	-----------------

Electric motor / moteur électrique / elektromotor	3 kW
--	-------------



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice