



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



GP5V-DP

DOUBLE PLUNGER VERTICAL GROUT PUMP

Overall dimensions and weight

Width	400 mm	1'4''
Length	900 mm	2'11''
Height	1500 mm	4'11''
Weight	350 Kg	772 lb



TECHNICAL FEATURES

Single effect double plunger

Max flow rate

25 lt/min

6,6 gpm

Max flow rate @ 100 bar

8 lt/min

2,1 gpm

Min flow rate @ 2 bar

0,5 lt/min

0,13 gpm

Max pressure rate

100 bar

10 MPa

1450 PSI

Electric motor

5,5 kW

Suction diameter

3/4''

19,05 mm

Output diameter

1/2'

12,7 mm

Equipped with electrohydraulic proportional valves

Controlled by external PLC for fine performance management (OPTIONAL)

Equipped with electronic flowmeter to be connected to the PLC control unit (OPTIONAL)

Tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice