



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



MTW500 / MTW750

SPECIAL SLURRY MIXER TANK



Technical Features

Electronic load cell weighing system / système de pesage électronique / Wägeelektronik für Wägezellen			
Max hourly capacity / capacité horaire maximum / maximale Stundenleistung	12 m3	53 gpm	
Electric power consumption / consommation électrique / Stromverbrauch	15 kW - 35 kW		
MIXER			
Max capacity / capacité maximale / maximale Kapazität	750 lt	198 gal	
Pump motor / moteur de pompe / Pumpenmotor	11 kW (OPT. 18,5 kW)		
Max pump flow rate / pompe débit maximale / Pumpe maximale Durchflussrate	@1 bar	1500 lt/min	396 gpm
AIR COMPRESSOR			
Air compressor capacity / capacité du compresseur d'air/ Luftverdichter Kapazität	250 lt/min	66 gpm	
Air tank / réservoir d'air / Luftbehälter	50 lt	13 gal	
Electric motor / moteur électrique / Elektromotor	1,5 kW		
SKID FRAME DIMENSIONS AND WEIGHT			
Width 2.200 mm - 7'2"	Lenght 2.400 mm - 7'10"	Height 2.200 mm - 7'2"	Weight 2400 kg - 5291 lb
CONTROL PANEL			
Electronic control panel with 7" display PLC – daily registration on USB key			
Panneau de commande électronique avec 7 " display PLC - enregistrement de la journée sur USB clé			
Elektronisches Bedienfeld mit 7" display PLC – täglich Registrierung mit USB Stift			



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice