



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



TWA 1500

HOLDING TANK



Skid frame dimensions and weight

Width	1800 mm	5'10"
Lenght	2200 mm	7'2"
Height	2200 mm	7'2"
Weight	1300 Kg	2866 lb

Technical Features

Electric power consumption / consommation électrique / Stromverbrauch	6 kW - 18 kW		
AGITATOR			
Max capacity / capacité maximale / maximale Kapazität	1500 lt	396 gal	
Electric motor / moteur électrique / elektromotor	2,2 Kw		
BOOSTER PUMP (standard)			
Max pump flow rate / pompe débit maximale / Pumpe maximale Durchflussrate	@1 bar	700 lt/min	185 gpm
Pump motor / moteur de pompe / Pumpenmotor	2,2 kW		
BOOSTER PUMP (optional)			
Max pump flow rate / pompe débit maximale / Pumpe maximale Durchflussrate	@1 bar	1200 lt/min	317 gpm
Pump motor / moteur de pompe / Pumpenmotor	11 kW		
AIR COMPRESSOR (optional, only for automatic version)			
Air compressor capacity / capacité du compresseur d'air/ Luftverdichter Kapazität	400 lt/min	105 gpm	
Air tank / réservoir d'air / Luftbehälter	100 lt	26,4 gal	
Electric motor / moteur électrique / Elektromotor	2,2 kW		



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
 e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice