



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



TWA 20

BENTONITE HOLDING TANK



Skid frame dimensions and weight

Width	2435mm	7'11"
Lenght	6055 mm	19'10"
Height	2540 mm	8'4"
Weight	4200 Kg	9259 lb

Technical Features

Electric power consumption / consommation électrique / Stromverbrauch	6 kW - 18 kW		
AGITATOR			
Max capacity / capacité maximale / maximale Kapazität	20000 lt	5283 gal	
Electric motor / moteur électrique / elektromotor	3 x 2,2 Kw		
RECIRCULATION / BOOSTER PUMP (standard)			
Max pump flow rate / pompe débit maximale / Pumpe maximale Durchflussrate	@1 bar	1900 lt/min	500 gpm
Pump motor / moteur de pompe / Pumpenmotor	11 kW		
ADDITIONAL RECIRCULATION / BOOSTER PUMP (optional)			
Max pump flow rate / pompe débit maximale / Pumpe maximale Durchflussrate	@1 bar	1900 lt/min	500 gpm
Pump motor / moteur de pompe / Pumpenmotor	11 kW		



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice