



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



TWM30/V

GROUT MIXER PLANT

Container 20' dimensions and weight

Width	2438 mm	7'12"
Lenght	6055 mm	19'10"
Height	2591 mm	8'6"
Weight	6000 Kg	13227 lb



Technical Features

Electronic load cell weighing system / système de pesage électronique/ Wägeelektronik für Wägezellen			
Max hourly capacity / capacité horaire maximum / maximale Stundenleistung	30 m³	132 gpm	
Electric power consumption / consommation électrique / Stromverbrauch	55-60 kW		
MIXER			
Max capacity / capacité maximale / maximale Kapazität	1300 lt	340 gal	
Max pump flow rate / pompe débit maximale / pompe maximale Durchflussrate	@1 bar	2000 lt/min	528 gpm
Pump motor / moteur de pompe / Pumpenmotor	15 kW		
Recirculation - Transfer line / Recirculation - ransfert ligne / Rezirkulation - Transfer Linie	3" - DN100		
AGITATOR			
Max capacity / capacité maximale / maximale Kapazität	2600 lt	687 gal	
Electric motor / moteur électrique / Elektromotor	2,2 Kw		
WATER TANK			
Max capacity / capacité maximale / maximale Kapazität	1600 lt	422 gal	
BOOSTER PUMP			
Max pump flow rate / pompe débit maximale / Pumpe maximale Durchflussrate	@1 bar	700 lt/min	185 gpm
Pump motor / moteur de pompe / Pumpenmotor	2,2 kW		
AIR COMPRESSOR			
Air compressor capacity / capacité du compresseur d'air/ Luftverdichter Kapazität	400 lt/min	105 gpm	
Air tank / réservoir d'air / Luftbehälter	100 lt	26,4 gal	
Electric motor / moteur électrique / Elektromotor	2,2 kW		
Set for horizontal silo stacking and CSC certificate			



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice